

SINCE 1977

LIVE FISH ELEVATOR

ORIGINAL SYSTEM

ELEVATOR 77 ALU CLASS



Machine is delivery with a motor with speed variator, thermal protection and wise reverser.



FAIVRE Research Department has designed these elevators with an Aluminium frame to be :

- Light (150 to 220 kg) and easily moved by a single operator.
- Ideal to load a grader, decant ponds, containers...
- Reliable due to its compact & simple design.
- High quality at an affordable price.

General characteristics :

77 ALU CLASS Ø330 mm :

- ⇨ Transparent polyester screw ø 330 mm.
- ⇨ Tonnage figure up to 5 t/h (adjustable with the motor variator)
- ⇨ Motor with speed variator : 0.55 kw 3 phases or 220V 1 phase.
- ⇨ Wheel carriage with adjustable height columns.

77 ALU CLASS Ø450 mm :

- ⇨ Transparent polyester screw ø450 mm.
- ⇨ Tonnage figure 0.5 à 8 t/h (adjustable with the motor variator)
- ⇨ Motor with speed variator : 0.55 kw 3 phases or 220V 1 phase.
- ⇨ Wheel carriage with adjustable height columns.

Strong points :

- ✓ Light and easy to handle machine.
- ✓ Ideal installed on sea cages.



77 ALU CLASS	Ø 330 mm		Ø 450 mm	
For Trout from...	5gr to 1,5kg	5gr to 1,5kg	5gr to 3,5kg	5gr to 3,5kg
For Bass & Bream from...	-	-	5gr to 2kg	5gr to 2kg
For Tilapia from...	-	-	5gr to 2kg	5gr to 2kg
Hourly tonnage adjustable (T/h)	0,5 to 5	0,5 to 5	0,5 to 8	0,5 to 8
Screw length (m)	4	5	4	5
Weight (kg)	150	170	200	220
Vertical lifting height (m) with 40° slope screw	1,9	2,5	1,9	2,5
References	F773AL4	F773AL5	F774AL4	F774AL5

1ST LET YOUR FISH TRAVEL FIRST CLASS



77 ALU CLASS Ø450 mm elevator working on sea cages.



77 ALU CLASS Ø330 mm elevator working at land based trout farm.

Pictures and technical data. are not contractual FAIVRE Sarl can also bring any modification to its equipment at any time.