



DRUM FILTER serie 60 - SS Tank



DRUM FILTER Serie 60 with Stainless steel tank

Flow rate up to 16 l/s (58m³/h) with 100μ.

It can be quickly installed in cramped places due to its low size and weight.

It is suitable for little closed circuits, laboratories, testing station etc...

No corrosion due to its stainless steel tank.

Its 60 cm diameter drum operates at 5 rpm.



☆ Stainless steel fabric ☆
high quality

Strong points :

- ✓ A rinsing system optimized so as to make water saving.
- ✓ A machine entirely made of AISI 304L (fresh water) or AISI 316L stainless steel.
- ✓ A machine of simple design and robust construction.
- ✓ A maintenance free solution.



*Drive and suspension of the drum by belts.
(Simple and robust solution)*

Table giving water volumes handled (l/s)

Filter model :	2-60	
	Filter plates mesh	
	26μ	8
Water with maxi 10 mg/l of waste Outlet fish farm	36μ	14
	40μ	15
	63μ	16
	80μ	16
	100μ	16
D R U M F I L T E R W I T H T A N K		
	26μ	7
Water with maxi 25 mg/l of waste Recirculation system	40μ	10
	60μ	15
	80μ	16
	<i>In case of waste over 25 mg/l , please consult us.</i>	
Motor power 3x400v (w)	250	
Rinsing at 3 bars 80μ (l/s)	0,18	
Filter surface (m2)	0,5	
Number of plates	2	



Pictures and technical data are not contractual. FAIVRE Sarl can bring any modification to its equipment at any time.