

# FAIVRE



## DRUM FILTER serie 60 - SS Tank



Maintenance free



### DRUM FILTER Serie 60 with Stainless steel tank

Flow rate up to 16 l/s (58m<sup>3</sup>/h) with 100 $\mu$ .

It can be quickly installed in cramped places due to its low size and weight.

It is suitable for little closed circuits, laboratories, testing station etc...

No corrosion due to its stainless steel tank.

Its 60 cm diameter drum operates at 5 rpm.

### Strong points :

- ✓ A rinsing system optimized so as to make water saving.
- ✓ A machine entirely made of AISI 304L (fresh water) or AISI 316L stainless steel.
- ✓ A machine of simple design and robust construction.
- ✓ A maintenance free solution.



☆ STAINLESS STEEL MESH ☆  
HIGH QUALITY



Drive and suspension of the drum by belts.  
(Simple and robust solution)

### Table giving water volumes handled (l/s)

Filtre modèle :		2-60	4-60
	Mesh size		
Water with maxi 10 mg/l of waste Outlet fish farm	26μ	8	16
	36μ	14	16
	63μ	16	16
	80μ	16	16
	100μ	16	16
<b>DRUM FILTER WITH TANK Ø160mm inlet and outlet pipe</b>			
Water with maxi 25 mg/l of waste Recirculation system	30μ	7	14
	40μ	10	16
	60μ	15	16
	80μ	16	16
In case of waste over 25 mg/l , please consult us.			
Motor power 3x400v (w)		250	250
Rinsing at 3 bars 80μ (l/s)		0,18	0,36
Filter surface (m2)		0,5	1
Number of plates		2	4



Pictures and technical data are not contractual. FAIVRE Sarl can bring any modification to its equipment at any time.